

## IK - zaślepka, stopka



**Kategoria :** Zaślepki

**Rodzaj profilu:**  
Okrągły

**Rodzaj montażu:**  
Wewnętrzny

**Materiał:**  
Polietylen

**Kolor:**  
Czarny, biały, popielaty

Art. nr	Zew. wymiar profilu /mm/	Grubość ścianki /mm/	Wymiar H /mm/	Wymiar L /mm/	Opak. szt.
IK10	10.0	1.0-2.0	3.5	6.9	1000
IK12	12.0	1.0-2.0	4.0	10.0	1000
IK13	13.0	1.0-2.0	4.0	10.0	1000
IK14	14.0	1.0-2.0	3.5	9.5	1000
IK15	15.0	1.0-2.0	4.4	9.0	1000
IK16	16.0	1.0-2.0	4.2	9.0	500
IK18	18.0	1.0-2.0	4.3	12.0	500
IK18	19.0	1.0-2.0	6.2	12.0	500
IK19	20.0	1.0-2.0	4.3	11.2	500
IK20	20.0	1.0-2.0	5.0	11.8	500
IK20	22.0	1.0-2.0	7.3	11.8	500
IK22	25.0	1.0-2.0	4.0	11.8	500
IK25	25.0	1.0-2.0	5.0	12.0	500
IK25	25.0	1.0-2.0	5.5	11.8	500
IK25	25.0	1.0-2.0	8.0	11.5	500
IK27	27.0	1.0-2.0	5.0	13.8	100
IK28	28.0	1.0-2.0	5.0	14.0	100
IK30	30.0	1.0-2.0	5.0	14.0	100
IK32	32.0	1.0-2.0	5.0	14.6	100
IK33	33.0	1.0-2.0	10.0	14.0	100

Art. nr	Zew. wymiar profilu /mm/	Grubość ścianki /mm/	Wymiar H /mm/	Wymiar L /mm/	Opak. szt.
IK34	34.0	1.0-2.0	5.0	14.5	100
IK35	35.0	1.0-2.0	5.0	14.0	100
IK36	36.0	1.0-2.0	6.5	13.9	100
IK38	38.0	1.0-2.0	5.5	11.5	100
IK40	40.0	1.0-2.0	6.0	12.0	100
IK42	42.0	1.0-2.0	6.0	12.0	100
IK45	45.0	1.0-2.0	5.0	15.0	100
IK48	48.0	1.5-2.5	6.0	18.0	100
IK50	50.0	1.5-2.5	6.0	16.0	100
IK55	55.0	1.0-2.0	6.0	14.0	100
IK60	60.0	1.5-2.5	6.0	21.4	100
IK80	80.0	1.5-3.0	5.5	22.0	50